

CYCLEMATIC

CNC TOOLROOM LATHE



**3-door type
splash guard**

CT-1118CNC

Specification

MODEL	CT-1118CNC
Maximum swing	280 mm (11")
Maximum turning diameter	152 mm (6")
Maximum turning length	457 mm (18")
Bar stock diameter (5C collet)	Ø27 mm (Ø1-1/16")
Hole through spindle	Ø31.75 mm (Ø1-1/4")
CNC controller	Optional
Spindle speeds (variable)	0~4000 RPM
Spindle nose I.D./O.D.	5C (10°) / 4° Taper
Chuck diameter	Ø152 mm (Ø6")
Maximum X-axis travel	160 mm (6-1/4")
Maximum Z-axis travel	340 mm (13-1/2")
Rapid traverse	15 M/min
Inverter spindle motor	5 HP
X, Z-axis motor	As controller
Cutting fluid motor	1/8 HP
Tailstock spindle taper	MT No.2
Tailstock spindle travel	95 mm
Machine dimensions (L x W x H)	2050 x 950 x 1750 mm
Machine weight	1000 kgs



**CT-606CNC
GANG-TOOL TYPE**

Splash guard is available ▶



CT-1118CNC



CT-1118CNC

◀ **4-door type splash guard**

EVS Series

TOOLROOM LATHE



CTL-618EVS



CTS-27EVS



CTL-27EVS



CHR-68EVS



CP-27EVS

CYCLEMATIC



EMO
Hannover
12-19-9-2001

Hall: 20 Stand: E12

CYCLEMATIC MACHINERY CO., LTD.

20, LANE 50, MIN SHENG RD., SHEN KANG, TAICHUNG, TAIWAN.

TEL: 886-4-2562-5393, 2562-6509

FAX: 886-4-2562-0298

E-mail: matic88@ms77.hinet.net

Mobile: 886-0933-199-080

<http://www.cyclematic.com>

<http://www.toolrooms.com>

<http://www.cyclematic.com.tw>

<http://www.toolroom.com.tw>